

440gsm Frontlit Banner PVC (FB440)

A water fast laminated PVC banner that is specifically suited for frontlit applications.

TECHNICAL SPECIFICATION

	Value	T Method
Weight	440gsm	
Thickness	0.38mm	
Tensile Strength	450/550	
Tear Strength	80/95	

AVAILABLE SIZES

1372mm	(54")	x 50m	3" Core
1600mm	(62")	x 30m	3" Core

APPLICATIONS AND CHARACTERISTICS

- Suitable for high quality durable signage
- Good weather resistant
- For use with eco, eco+, eco ultra and solvent inks
- Accepts high ink coverage
- Excellent sharp colourful images

PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

MANUFACTURER

MODEL

INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

APPLICATION NOTES

High temperature resistance: -20°C to +70°C

STORAGE AND TRANSPORT

The ideal storage conditions for this product are 33-65% relative humidity with temperatures of +10°C to +25°C. We recommend that you always keep this product in its original packaging.

