

# 550gsm Frontlit PVC (FB550)

A Class 1 / B1 fire rated water fast laminated PVC banner that is specifically suited foer frontlit applications

## TECHNICAL SPECIFICATION

	Value	T Method
Weight	550gsm	
Thickness	0.38mm	
Tensile Strength	1000/900 N/5cm	DIN53354
Tear Strength	80/95 N/5cm	DIN53363

## AVAILABLE SIZES

1372mm	(54")	x 30m	3" Core
1600mm	(62")	x 30m	3" Core

## APPLICATIONS AND CHARACTERISTICS

- Class 1 / B1 fire rated
- Suitable for high quality durable signage
- Good weather resisence
- For use with Eco, Eco+, Eco ultra and solvent inks
- Smooth surface and excellent ink acceptance
- Vivid colour and high resolution

## PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

## MANUFACTURER

## MODEL

## INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

## APPLICATION NOTES

High temperature resistance: -20°C to +70°C

## STORAGE AND TRANSPORT

The ideal storage conditions for this product are 33-65% relative humidity with temperatures of +10°C to +25°C. We recommend that you always keep this product in its original packaging.