

# Mesh Banner PVC (MESH)

A very rip-proof mesh banner material with a large surface area to enhance images for more accurate colour reproduction

## TECHNICAL SPECIFICATION

|               | Value         | T Method |
|---------------|---------------|----------|
| Toal Weight   | 500gsm        |          |
| Tear Strength | 250/180 N/5cm | DIN53363 |

## AVAILABLE SIZES

|        |       |       |         |
|--------|-------|-------|---------|
| 1600mm | (63") | x 30m | 3" Core |
| 1372mm | (54") | x 30m | 3" Core |

## APPLICATIONS AND CHARACTERISTICS

- Excellent durable banner material
- Mesh construction to allow for good wind resistance
- For use with eco, eco+, eco ultra and solvent inks
- Protective release liner for ease of printing
- High surface area for long distance effect

## PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

## MANUFACTURER

## MODEL

## INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

## APPLICATION NOTES

The minimum application temperature is +5°C. The service temperature range is -10°C to +50°C.

## STORAGE AND TRANSPORT

The ideal storage conditions for this product are 33-65% relative humidity with temperatures of +10°C to +25°C. We recommend that you always keep this product in its original packaging.