

200mic Backlit Film (BLF200)

A front print 200 micron satin finish polyester film for solvent printing

TECHNICAL SPECIFICATION

	Value	T Method
Weight	270gsm	
Thickness	200µm	

AVAILABLE SIZES

914mm	(36")	x 30m	3" Core
1372mm	(54")	x 30m	3" Core
1524mm	(60")	x 20m	3" Core

APPLICATIONS AND CHARACTERISTICS

- Heavier weight for ease of handling
- Pure satin finish
- Best suited for indoor applications
- Built in light-diffusing layer
- Anti statically treated
- Compatible with Solvent, Eco solvent and UV curable inks

PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

MANUFACTURER

MODEL

INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

APPLICATION NOTES

The minimum application temperature is +5°C. The service temperature range is -10°C to +50°C.

STORAGE AND TRANSPORT

The ideal storage conditions for this product are 35-65% relative humidity with temperatures of +10°C to +30°C. We recommend that you always keep this product in its original packaging.