

# Solvent Pop Up Film (SPRO)

A 350micron rigid film with a solvent coating fro pop-up banners

## TECHNICAL SPECIFICATION

	Value	T Method
Thickness	350mic	

## AVAILABLE SIZES

914mm	(36")	x 20m	3" Core
1067mm	(42")	x 20m	3" Core
1270mm	(50")	x 20m	3" Core

## APPLICATIONS AND CHARACTERISTICS

- Single sided coated film with a high white matt coating
- Vibrant image reproduction
- Accepts high ink coverage
- Opaque white back for minimum show through
- For use with Solvent and Eco Solvent inks
- Can be laminated right up to the edges
- Excellent no curl properties

## PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

## MANUFACTURER

## MODEL

## INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

## APPLICATION NOTES

The minimum application temperature is +5°C. The service temperature range is -10°C to +50°C.

## STORAGE AND TRANSPORT

The ideal storage conditions for this product are 35-65% relative humidity with temperatures of +10°C to +30°C. We recommend that you always keep this product in its original packaging.