

225mic Self Adhesive Window Film (VTFSA)

A single-side coated, polyester film with a Matte coating. Suitable for eco & solvent inks. The adhesive is made specifically for indoor application.

TECHNICAL SPECIFICATION

	Value	T Method
Weight	230gsm	DIN 53104
Thickness	225mic	ISO 534
PH Value	7	DIN 53124

AVAILABLE SIZES

1270mm (50") x 20m 3" Core

APPLICATIONS AND CHARACTERISTICS

- Increased opacity to allow for both backlit and frontlit applications
- Fast drying time
- For use with Eco, Eco+, Eco Ultra and Solvent inks
- Good water resistance
- Excellent sharp, colourful images
- Easily mountable adhesive

PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

MANUFACTURER

MODEL

INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

APPLICATION NOTES

The minimum application temperature is +5°C. The service temperature range is -10°C to +50°C.

STORAGE AND TRANSPORT

The ideal storage conditions for this product are 35-65% relative humidity with temperatures of +10°C to +30°C. We recommend that you always keep this product in its original packaging.